

| <u>DRILL HOLE</u> | <u>FROM</u> | <u>TO</u> | <u>CORE LENGTH m</u> | <u>Sn ppm</u> | <u>W ppm</u> |
|-----------------------|-------------|-----------|--------------------------|---------------|--------------|
| SMD 4 | 68.37 | 95.90 | 27.53 | 1320 | 840 |
| | 0.00 | 95.90 | 95.90 | 380 | 240 |
| SMD 6 | 21.35 | 101.00 | 79.65 | 1100 | 960 |
| | 0.00 | 101.00 | 101.00 | 860 | 750 |
| SMD 7 | 0.00 | 45.35 | 45.35 | 1630 | 740 |
| SMD 10 | 38.75 | 76.00 | 37.25 | 1680 | 670 |
| | 0.00 | 76.00 | 76.00 | 820 | 330 |
| SMD 11 | 31.00 | 74.00 | 43.00 | 1450 | 960 |
| | 0.00 | 74.00 | 74.00 | 840 | 560 |
| SMD 15 | 33.00 | 103.00 | 70.00 | 1500 | 1270 |
| | 0.00 | 103.00 | 103.00 | 1020 | 860 |
| SMD 28 | 17.70 | 90.60 | 72.90 | 1680 | 850 |
| | 0.00 | 90.60 | 90.60 | 1350 | 680 |
| SMD 29 | 0.00 | 83.50 | 83.50 | 850 | 1760 |
| MD 40 | 10.00 | 85.20 | 75.20 | 1360 | 950 |
| MD 41 | 0.00 | 28.50 | 28.50 | 1560 | 820 |

These drill holes cover an area of approximately 500 m by 200 m across the thickest mineralized section. Part of this area is basalt covered, and beyond this area mineralization thins and basalt cover thickens. Drill hole sections along 1100 m E, 975 m E, 900 m E and 700 m E are plotted on plans D/MZ01/067, 116, 068, 107, 135, 136.