CENTURY GEOPHYSICAL CORPORATION OF AUSTRALIA

CLIENT: C.S.R.
WELL: RD75
AREA: LAUNCESTON
STATE: TAS.

HOLE DATA

| | | | |
|---|---|---|---|
| TOTAL DEPTH - DRILLER | 78m | BIT SIZE | 12¼" |
| TOTAL DEPTH - LOGGER | 76.5m | CASING - SIZE & WEIGHT | |
| CASING SHOE - DRILLER | 6m | CASING - GRADE & TYPE | |
| CASING SHOE - LOGGER | 6m | CEMENTED TO | |
| LOGGING ENGR. | M.HOW | CEMENTED FROM | H.O |
| METHOD USED | ROTARY | FLUID RESISTIVITY | |
| FROM W.L. | ROTARY | FLUID LEVEL | V.G.I |
| REMARKS | TAPE IS TRACES | EQUIPMENT NO. | |

EQUIPMENT DATA

| RECORDED | | | |
|---|---|---|---|
| | RUN 1 | RUN 2 | RUN 3 |
| LOGGING DATE | 27-7-82 | | |
| LOGGING UNIT | 2 | | |
| LOGGING ENGR. | M.HOW | | |
| OPERATOR | M.HOW | | |
| CALIBRATION DATE | 27-7-82 | | |
| CALIBRATION UNIT | 2 | | |
| CALIBRATION ENGR. | M.HOW | | |
| CALIBRATION OPERATOR | M.HOW | | |
| CALIBRATION WITNESS | | | |
| LOGGING DATA | | | |
| LOGGING SPEED | 3m/min | | |
| TIME CONSTANT | 1 SEC | | |
| DEPTH CONTROL | | | |
| DEPTH CORRECTION | | | |
| CABLE TYPE | | | |
| CABLE LENGTH | | | |
| PROBE TYPE | | | |
| PROBE SERIAL NO. | | | |
| PROBE DIAMETER | | | |
| PROBE LENGTH | | | |
| PROBE WEIGHT | | | |
| MEASURE POINT OFFSET | | | |
| REMARKS | | | |

| FIELD STRENGTH | | | |
|---|---|---|---|
| MAGNETIC DECLINATION | | | |
| GRID CORRECTION | | | |
| TYPE OF FIELD | | | |
| REMARKS | | | |

| RECEIVED | | | |
|---|---|---|---|
| | RUN 1 | RUN 2 | RUN 3 |
| RECEIVED AT | HOBART | | |
| RECEIVED DATE | 28-7-82 | | |
| PROCESSED BY | | | |
| PROCESSING DATE | | | |
| REMARKS | | | |

RD75 27-7-82
M. How
S2




COMPILATION VOL 2 PLOT 83-28-82

RD75
C.S.R.
LAUNCESTON
HOLE DIAMETER : 12.0
PROBE # 0023(1-898
SCANSON #4 CAL STD CPS = 4388
SCANSON #4 CAL RUN CPS = 5072
SCANSON #4 CAL BIAS = 0
BATH VOL1 THICK = 8098
BATH CHECK METL WIDTH =