

MAGNETIC SUSCEPTIBILITY								BULK ASSAYS								REMARKS						
M	K	M	K	M	K	M	K	%FeS <sub>2</sub>	Agm/mT	Agm/mT			From	To	m.		%Cu	%FeS <sub>2</sub>	Agm/mT	Agm/mT		
3.0	1.3	78.0	0.1	150.0	1.0	222.0	0.3														K = Direct reading from a Stainless Steel Magnetic Susceptibility Meter x 10 <sup>-3</sup> cgs	
6.0	0.1	80.0	0.1	152.0	0.3	224.0	1.9															
8.0	0.1	82.0	0.1	154.0	0.3	226.0	0.1															
10.0	0.1	84.0	0.0	156.0	1.3	228.0	1.5															
12.0	0.1	86.0	0.0	158.0	1.2	230.0	2.3															
14.0	0.4	88.0	0.1	160.0	1.0	232.0	0.0															
16.0	0.1	90.0	0.1	162.0	3.7	234.0	0.0															
18.0	0.1	92.0	0.1	164.0	4.8	236.0	0.4															
20.0	0.1	94.0	0.0	166.0	5.3	238.0	2.3															
22.0	0.0	96.0	0.1	168.0	0.1	240.0	2.3															
24.0	0.1	98.0	0.2	170.0	3.8	242.0	0.4															
26.0	0.0	100.0	0.1	172.0	4.9	244.0	0.0															
28.0	0.1	102.0	0.1	174.0	0.0	246.0	1.5															
30.0	0.1	104.0	0.0	176.0	0.6	248.0	1.2															
32.0	0.0	106.0	0.0	178.0	0.0	250.0	3.4															
34.0	0.1	108.0	0.0	180.0	0.0																	
36.0	0.0	110.0	0.4	182.0	0.0																	
38.0	0.0	112.0	0.3	184.0	2.9																	
40.0	0.0	114.0	2.5	186.0	4.3																	
42.0	0.0	116.0	2.3	188.0	1.9																	
44.0	0.0	118.0	0.3	190.0	1.8																	
46.0	0.0	120.0	4.1	192.0	1.6																	
48.0	0.0	122.0	2.8	194.0	0.2																	
50.0	0.0	124.0	0.1	196.0	0.8																	
52.0	0.0	126.0	1.5	198.0	0.3																	
54.0	0.0	128.0	0.3	200.0	0.8																	
56.0	0.0	130.0	1.4	202.0	0.1																	
58.0	0.1	132.0	0.6	204.0	0.1																	
60.0	0.0	134.0	0.1	206.0	0.0																	
64.0	0.0	136.0	1.0	208.0	5.0																	
66.0	0.1	138.0	3.0	210.0	1.4																	
68.0	0.0	140.0	2.6	212.0	2.7																	
70.0	0.0	142.0	3.1	214.0	1.2																	
72.0	0.0	144.0	2.3	216.0	4.3																	
74.0	0.0	146.0	2.5	218.0	0.5																	
76.0	0.1	148.0	0.2	220.0	2.5																	