

THE MOUNT LYELL MINING AND RAILWAY COMPANY LIMITED

APPENDIX P Continued

ADVANCE		RECOVERY		ROD		ASSAYS										Fire Assay		A.S.S.								
From	To	m	%	m	%	From	To	m	Cu	Pb	Zn	Ag	Mn	Co	Ag	As	%S	%FeS2	Au g/mT	Ag g/mT	SG					
61.6	63.3	1.7	136%	-	-	61.6	63.3	1.7	136%	-	130	5	10000	10	1.3	5.0	-	-	-	-	-	-	-	-	-	-
	65.0	1.7	0.76%	10	130	65.0	66.0	1.0	1.06%	30	320	9	2300	90	2.0	3.6	1.0	-	-	-	-	-	-	-	-	-
	66.0	1.0	1.06%	30	320	66.0	67.0	1.0	1.38%	30	200	6	6200	20	5.3	5.8	1.3	-	-	-	-	-	-	-	-	-
	67.0	1.0	1.38%	30	200	67.0	68.0	1.0	1.58%	40	140	6	7200	10	1.0	5.6	1.9	-	-	-	-	-	-	-	-	-
	68.0	1.0	1.58%	40	140	68.0	69.0	1.0	2.72%	20	120	10	1000	10	1.0	9.6	1.8	-	-	-	-	-	-	-	-	-
	69.0	1.0	2.72%	20	120	69.0	70.0	1.0	2.80%	30	220	3	1200	20	0.6	2.5	2.0	-	-	-	-	-	-	-	-	-
	70.0	1.0	2.80%	30	220	70.0	71.0	1.0	2.12%	40	230	8	1300	20	1.9	7.2	2.2	-	-	-	-	-	-	-	-	-
	71.0	1.0	2.12%	40	230	71.0	72.0	1.0	1.96%	40	240	6	1400	10	0.5	4.7	1.6	-	-	-	-	-	-	-	-	-
	72.0	1.0	1.96%	40	240	72.0	73.0	1.0	2.96%	70	240	9	1000	10	1.0	7.7	2.3	-	-	-	-	-	-	-	-	-
	73.0	1.0	2.96%	70	240	73.0	74.0	1.0	2.26%	50	240	8	1600	20	1.2	6.5	2.8	-	-	-	-	-	-	-	-	-
	74.0	1.0	2.26%	50	240	74.0	75.0	1.0	1.98%	50	210	6	1100	20	2.9	5.6	2.1	-	-	-	-	-	-	-	-	-
	75.0	1.0	1.98%	50	210	75.0	76.0	1.0	0.76%	50	210	3	1000	10	0.3	1.7	0.7	-	-	-	-	-	-	-	-	-
	76.0	1.0	0.76%	50	210	76.0	77.0	1.0	1600	30	230	2	850	50	0.2	0.7	0.9	-	-	-	-	-	-	-	-	-
	77.0	1.0	1600	30	230	77.0	78.0	1.0	1200	40	230	-	1100	40	NA	NA	0.4	-	-	-	-	-	-	-	-	-
	78.0	1.0	1200	40	230	78.0	79.0	1.0	1600	30	220	-	800	30	1	1	0.4	-	-	-	-	-	-	-	-	-
	79.0	1.0	1600	30	220	79.0	80.0	1.0	300	30	190	-	650	40	1	1	0.3	-	-	-	-	-	-	-	-	-
	80.0	1.0	300	30	190	80.0	85.0	5.0	410	40	170	-	1000	30	1	1	0.1	-	-	-	-	-	-	-	-	-
	85.0	5.0	410	40	170	85.0	90.0	5.0	250	20	110	-	400	20	1	1	0.4	-	-	-	-	-	-	-	-	-
	90.0	5.0	250	20	110	90.0	95.0	5.0	210	20	120	-	550	-	1	1	0.3	-	-	-	-	-	-	-	-	-
	95.0	5.0	210	20	120	95.0	100.0	5.0	140	20	110	-	500	10	1	1	-	-	-	-	-	-	-	-	-	-
	100.0	5.0	140	20	110	100.0	105.0	5.0	10	20	100	-	250	-	1	1	-	-	-	-	-	-	-	-	-	-
	105.0	5.0	10	20	100	105.0	110.0	5.0	90	20	110	-	500	20	1	1	0.4	-	-	-	-	-	-	-	-	-
	110.0	5.0	90	20	110	110.0	115.0	5.0	760	50	90	-	590	10	1	1	0.3	-	-	-	-	-	-	-	-	-
	115.0	5.0	760	50	90	115.0	120.0	5.0	2200	100	110	-	700	10	1	1	0.4	-	-	-	-	-	-	-	-	-
	120.0	5.0	2200	100	110	120.0	125.0	5.0	250	30	80	-	620	20	1	1	0.2	-	-	-	-	-	-	-	-	-
	125.0	5.0	250	30	80	125.0	130.0	5.0	570	100	140	-	1100	-	1	1	-	-	-	-	-	-	-	-	-	-
	130.0	5.0	570	100	140	130.0	135.0	5.0	300	50	130	-	640	-	1	1	0.3	-	-	-	-	-	-	-	-	-
	135.0	5.0	300	50	130	135.0	140.0	5.0	960	210	200	-	1200	-	1	1	0.3	-	-	-	-	-	-	-	-	-
	140.0	5.0	960	210	200	140.0	145.0	5.0	1050	350	200	-	1300	-	1	1	-	-	-	-	-	-	-	-	-	-
	145.0	5.0	1050	350	200	145.0	150.0	5.0	1500	30	180	-	620	30	1	1	0.4	-	-	-	-	-	-	-	-	-
	150.0	5.0	1500	30	180	150.0	155.0	5.0	2200	120	210	-	700	30	1	0.9	0.4	-	-	-	-	-	-	-	-	-
	155.0	5.0	2200	120	210	155.0	158.3	3.3	2100	90	290	-	1200	40	1	1.3	0.6	-	-	-	-	-	-	-	-	-
	158.3	3.3	2100	90	290	Detection Limit :		10	10	10	2	10	10	0.1	0.1	0.1%	NA - NOT ASSAYED	-	-	-	-	-	-	-	-	-