


CHARGEABILITY
 TRANSMITTER: SCINTREX 25/3 KW TIME DOMAIN
 I.P. TRANSMITTER
 RECEIVERS: SCINTREX IPR-8 RECEIVERS
 CYCLE: ALTERNATING SQUARE WAVE 8
 SECONDS PER CYCLE (2 SECS. ON-
 2 OFF- 2 ON, REVERSE POLARITY-
 2 OFF)
 RECEIVER DIPOLE: 20m
 STATION INTERVAL: 20m, PLUS SOME INTERMEDIATE
 STATIONS
 PLOTTING POINT: MID-POINT OF RECEIVER DIPOLE
 SURVEY DATES: 5TH, 6TH, 7TH & 10TH, FEB., 1982



- TRENCHES
- RIVER CREEK
- △ PROMINENT PEAK
- △ TRIG STATION
- ⊙ BENCH MARK
- SPOT ELEVATIONS
- PIT
- COSTEAN TRENCH
- ≡ ADIT
- ⊠ SHAFT (Depth metre)
- ⊕ OPEN CUT
- ⊗ ALLUVIAL WORKINGS
- ⊞ DUMP

THE MOUNT LYELL MINING & RAILWAY COMPANY LTD.

**JUKES PTY GRID
 GRADIENT ARRAY I.P.
 CHARGEABILITY**

SCALE 1:5000
 DATE 18.4.82
 DRAWN BY M. HUTTON
 CHECKED BY S. FIEBER
 FIG. 75
 A2-201-9