

A P P E N D I X ATHE FLIGHT RECORD AND PATH RECOVERY

Both analog and digital flight records are produced. The analog profiles are recorded on green chart paper in the aircraft during the survey. The digital profiles are generated later by computer and plotted on electrostatic chart paper at 1:15,000 or at map scale, whichever is larger. The digital profiles, which may be displayed, are as follows:

<u>Channel Number</u>	<u>Parameter</u>	<u>Scale units/mm</u>
20	magnetics	10 gamma
21	bird height	3 m
22	vertical coaxial coil-pair inphase (freq #1)	1 ppm
23	vertical coaxial coil-pair quadrature (freq #1)	1 ppm
24	horizontal coplanar coil-pair inphase (freq #2)	1 ppm
25	horizontal coplanar coil-pair quadrature (freq #2)	1 ppm
26	VLF-EM total field	1 %
27	VLF-EM vertical quadrature	1 %
28	ambient noise monitor (coaxial receiver)	1 ppm
29	ambient noise monitor (coplanar receiver)	1 ppm
33	difference function inphase from channels 22 and 24	1 ppm
34	difference function quadrature from channels 23 and 25	1 ppm
35	first anomaly recognition function	1 ppm
36	second anomaly recognition function	1 ppm
37	conductance	1 mho
40	log resistivity (at freq #2)	.03 decade
41	apparent depth or thickness (at freq #2)	3 m
42	conductivity contrast (at freq #2)	arbitrary
43	depth contrast (at freq #2)	arbitrary
44	product 42*43 (at freq #2)	arbitrary
45	log resistivity (at freq #1)	.03 decade
46	apparent depth or thickness (at freq #1)	3 m
47	conductivity contrast (at freq #1)	arbitrary
48	depth contrast (at freq #1)	arbitrary
49	product 47*48 (at freq #1)	arbitrary
50	apparent weight percent magnetite	0.25%