



N.B. CHARGEABILITY PLOTTED IS SLICE FROM 510 - 1050 msec.
CHARGEABILITY IN msec.

5 cm

KT 27/76-3
(1:10000)

| | | | |
|---|---|---|---|
| 1 | 2 | 1 | 2 |
| 3 | 4 | 3 | 4 |
| 1 | 2 | 1 | 2 |
| 3 | 4 | 3 | 4 |

WRT B/L SERIES

KT 27/76-5
(1:10000)

| | | | |
|---|---|---|---|
| 1 | 2 | 1 | 2 |
| 3 | 4 | 3 | 4 |
| 1 | 2 | 1 | 2 |
| 3 | 4 | 3 | 4 |

PSEUDOSECTION SHEET DIVISION (1:2500)

R
B
C

GN MN
15°00'

GEOPEKO
A DIVISION OF PEKO-WALLSEND OPERATIONS LTD.

Scale 1:5000

25 0 25 50 75 100 125 150 175 200 225 250
metres

DRAWING NO. SHEET NO 55E4-28

GEO J.S.
DATE Feb. 83
DRAWN P.R.S.
CONT INT 2 msec
INST Rx IPR 11
INST Tx Mumac 2.5kW
OBSER R.G.D.W.

E.L.27/76 ELLIOTT BAY TASMANIA
PSEUDOSECTION OF DIPOLE - DIPOLE
APPARENT CHARGEABILITY
DIPOLE SPACING 50m