

an error in flight path recovery. The resulting flight path locations therefore reflect a more stringent checking than is normally provided by manual flight path recovery techniques.

Table A-1. The Digital Profiles

<u>Channel Name (Freq)</u>	<u>Observed parameters</u>	<u>Scale units/mm</u>
MAG	magnetics	10 nT
ALT	bird height	3 m
CXI (900 Hz)	vertical coaxial coil-pair inphase	1 ppm
CXQ (900 Hz)	vertical coaxial coil-pair quadrature	1 ppm
CXS (900 Hz)	ambient noise monitor (coaxial receiver)	1 ppm
CPI (900 Hz)	horizontal coplanar coil-pair inphase	1 ppm
CPQ (900 Hz)	horizontal coplanar coil-pair quadrature	1 ppm
CPS (900 Hz)	ambient noise monitor (coplanar receiver)	1 ppm
CPI (7200 Hz)	horizontal coplanar coil-pair inphase	1 ppm
CPQ (7200 Hz)	horizontal coplanar coil-pair quadrature	1 ppm
CPS (7200 Hz)	ambient noise monitor (coplanar receiver)	1 ppm
<u>Computed Parameters</u>		
DIFI (900 Hz)	difference function inphase from CXI and CPI	1 ppm
DIFQ (900 Hz)	difference function quadrature from CXQ and CPQ	1 ppm
REC1	first anomaly recognition function	1 ppm
REC2	second anomaly recognition function	1 ppm
REC3	third anomaly recognition function	1 ppm
REC4	fourth anomaly recognition function	1 ppm
CDT	conductance	1 grade
RES (900 Hz)	log resistivity	.03 decade
RES (7200 Hz)	log resistivity	.03 decade
DP (900 Hz)	apparent depth	3 m
DP (7200 Hz)	apparent depth	3 m
FEO% (900 Hz)	apparent weight percent magnetite	0.25%