

## RECEIVER

The UTEM 3 receiver is functionally the same as the UTEM 2 receiver in routine operation. It has many added switch selectable options for special applications and the convenience of experienced operators who want to optimize survey efficiency. The front panel is substantially the same as that of UTEM 2, except for the elimination of a few controls. The added options can be set by alternate use of the same controls as indicated by a second function mask in the receiver cover. The new features added are the result of more than 2000 line-km of surveying with the UTEM 2 prototype.

The most visible changes from UTEM 2 are reductions in size, weight and power consumption, and a more sturdy, field worthy construction.

In common with UTEM 2, the UTEM 3 receiver is a digital stacking instrument, which automatically "prunes" out noisy cycles and records the data with a built in low power digital cassette recorder. The recording media are inexpensive digital grade cassettes capable of storing more than two weeks of data. A 6 digit label lets the operator set a recorded label pointing to the position of the survey station (line number and station number). All relevant switch settings such as gains, type of input, etc. are also recorded with the ten channel measurements. These settings are also internally protected against any change during stacking until they <sup>are</sup> recorded or manually rejected. Audio tones inform the operator of the status of the receiver (idle, stacking, recording) and warns him of any operating errors. An analog meter is provided for monitoring the data precision, but it is not meant for note taking since this is handled by the tape recorder. As the stacking progresses, the continuous average of any channel can be monitored. A steady reading indicates that enough averaging was done. The operator can stop the stacking manually or set automatic averaging limits. Data can be recorded automatically after stacking, or by a manual control after inspection. The receiver can also be set to do a selectable number of stacking/recording cycles automatically at timed intervals if required. The meter can also be used for monitoring any receiver