

ELECTROLYTIC ZINC COMPANY OF ASIA LTD. MINERAL RESOURCES DIVISION - TASMANIA						DIAMOND DRILL CORE GEOCHEMICAL ANALYSES RECORD													HOLE No. DDH CHP 267 SHEET No. 1			
LABORATORY ANALYTICAL TECHNIQUE DETECTION LIMIT						ANALABS													GRID CO-ORDS: A.M.G. CO-ORDS: 5,370,784mN 375,792mE COLLAR R.L.: 297m COLLAR DIP: -45° AZIMUTH: 090° AMG TOTAL DEPTH: 133.5m			
						402	401	309	108	402	108	114	108	108	108	108	108	108	108		GRID CO-ORDS:	A.M.G. CO-ORDS:
						XRF	XRF	Fire Assay	AAS	XRF	AAS	AAS	AAS	AAS	AAS	AAS	AAS	AAS	AAS		COLLAR R.L.:	COLLAR DIP:
						3	10	0.008	0.5	3	10	1	5	5	5	50	5	5		AZIMUTH:	TOTAL DEPTH:	
Sample No.	Sample Type	From	To	Core Rec'd	Sample Length	METAL CONTENT (ppm unless specified)													COMMENTS			
						Sn	W	Au	Ag	Sb	Bi	As	Cu	Pb	Zn	Fe%	Mn	Cr				
63534	Chip	9.0	12.0	3.0	3.0	8	X	X	X	9	X	37	30	X	25	2.05	335	25	Quartz-pyrite veins; 5-10% Pyrite			
535	"	12.0	15.0	3.0	3.0	10	X	X	X	5	X	21	25	X	75	2.15	275	35				
536	"	15.0	17.0	2.0	2.0	9	X	X	0.5	X	X	11	20	X	35	1.30	190	20				
537	"	17.0	18.8	1.8	1.8	X	X	X	0.5	3	X	16	25	X	30	1.55	285	40				
538	"	18.8	21.5	2.7	2.7	11	X	X	X	7	X	18	15	X	30	1.25	240	30				
539	"	21.5	23.7	2.2	2.2	21	X	X	X	X	X	6	15	X	15	1.40	265	30				
63540	Split	23.7	24.35	0.65	0.65	1.01%	25	X	0.5	X	X	210	60	X	10	2.55	170	80				
541	Chip	24.35	27.3	2.95	2.95	205	X	0.06	0.5	5	X	40	30	X	10	1.55	215	35				
542	"	27.3	30.6	3.3	3.3	9	X	0.01	0.5	4	X	20	25	X	20	2.15	365	95				
543	"	30.6	32.9	2.3	2.3	X	X	X	0.5	X	X	X	10	5	20	1.50	250	65				
544	"	32.9	36.0	3.1	3.1	X	X	X	0.5	X	X	X	15	X	30	2.10	270	70				
545	"	36.0	39.0	3.0	3.0	X	X	X	1.0	9	X	69	20	10	20	3.25	250	40				
546	"	39.0	40.2	1.2	1.2	4	X	X	0.5	3	X	2	25	X	20	2.10	240	85				
547	"	40.2	42.8	2.6	2.6	3	X	X	X	11	X	15	60	X	25	2.90	655	140				
548	"	42.8	44.4	1.6	1.6	3	X	X	X	11	X	16	20	5	20	2.65	805	105				
549	"	44.4	47.1	2.7	2.7	X	X	X	0.5	7	X	14	20	5	40	2.05	390	130				
63550	"	47.1	50.0	2.9	2.9	X	X	X	X	X	X	4	30	5	30	1.85	510	100				
551	"	50.0	52.6	2.6	2.6	X	X	X	X	X	X	3	20	X	25	2.40	865	90				
552	"	52.6	55.1	2.5	2.5	X	X	X	X	X	X	X	25	X	25	1.95	670	155				
553	"	55.1	57.6	2.5	2.5	X	X	X	X	X	X	X	10	X	20	1.75	805	160				
554	"	57.6	60.6	3.0	3.0	X	X	X	0.5	3	X	4	20	X	20	1.75	825	85				
555	"	60.6	63.6	3.0	3.0	8	X	X	0.5	25	X	19	25	15	15	2.35	405	50				
556	"	63.6	65.9	2.3	2.3	X	X	X	0.5	11	X	20	25	5	20	2.65	475	50				
557	"	65.9	68.3	2.4	2.4	9	X	X	0.5	X	X	220	10	20	85	1.70	1050	145				
558	Split	68.3	69.0	0.7	0.7	89	22	X	X	11	X	900	110	275	49	2.75	1.20%	105				
559	"	69.0	69.5	0.5	0.5	31	X	X	X	22	X	33	40	75	270	3.80	4200	90				
63560	"	69.5	70.5	1.0	1.0	20	X	X	0.5	9	X	55	50	X	55	2.85	625	75				
561	"	70.5	71.5	1.0	1.0	18	X	X	0.5	9	X	19	25	5	15	1.80	505	125				
562	"	71.5	72.3	0.8	0.8	15	X	X	0.5	7	X	16	30	X	85	2.45	1400	65				
563	Chip	72.3	75.0	2.7	2.7	8	X	X	X	12	X	14	45	X	20	2.45	1000	80				
564	"	75.0	76.55	1.55	1.55	X	X	X	1.0	29	X	41	65	20	20	2.55	510	55				
565	Split	76.55	77.2	0.65	0.65	15	X	X	0.5	18	X	19	125	5	110	4.00	650	115				
566	"	77.2	78.2	1.0	1.0	15	X	0.01	X	24	X	44	45	15	75	3.05	530	110				
567	"	78.2	79.1	0.9	0.9	25	X	X	0.5	28	X	34	40	15	10	2.50	220	100				
568	"	79.1	80.1	1.0	1.0	12	X	X	X	37	X	67	55	20	20	2.95	395	65				
569	"	80.1	81.1	1.0	1.0	6	X	X	0.5	38	X	22	65	15	10	3.80	1100	60				
63570	"	81.1	81.95	0.85	0.85	19	X	X	0.5	47	X	78	50	20	10	3.95	540	60				
571	"	81.95	82.2	0.25	0.25	46	X	0.02	X	22	X	80	30	5	20	9.95	125	170				
572	"	82.2	82.7	0.5	0.5	562	X	X	0.5	31	20	80	90	30	10	13.00	505	115				
573	"	82.7	83.0	0.3	0.3	100	X	X	X	11	X	140	255	15	10	10.50	975	195				
574	"	83.0	83.25	0.25	0.25	79	X	X	0.5	45	80	2650	30	85	10	21.00	235	125				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X	5	25	X	45	5.10	3600	95				
575	"	83.25	83.5	0.25	0.25	84	15	X	X	19	X	140	30	X	25	6.90	1350	160				
576	"	83.5	84.2	0.7	0.7	13	X	X	X	7	X	50	30	X	40	5.00	2250	125				
577	Chip	84.2	86.0	1.8	1.8	X	X	X	X	3	X											