

ELECTROLYTIC ZINC COMPANY OF A'ASIA LTD.
MINERAL RESOURCES DIVISION - TASMANIA

DIAMOND DRILL CORE GEOCHEMICAL ANALYSES RECORD

HOLE No. DDH CHP 268
SHEET No. 1

LABORATORY						ANALABS														GRID CO-ORDS: 371,600N	
ANALYTICAL TECHNIQUE						402	401	309	108	402	108	114	108	108	108	108	108	108	108	A.M.G. CO-ORDS: 375,485E	
DETECTION LIMIT						XRF	XRF	Fire Assay	AAS	XRF	AAS	AAS	AAS	AAS	AAS	AAS	AAS	AAS	COLLAR R.L.: 354m		
						3	10	0.008	0.5	3	10	1	5	5	5	50	5	5	COLLAR DIP: -60°		
						METAL CONTENT (ppm unless specified)														AZIMUTH: 270° AMG	
																				TOTAL DEPTH: 100.4m	
Sample No.	Sample Type	From	To	Core Rec'd	Sample Length	METAL CONTENT (ppm unless specified)														COMMENTS	
						Sn	W	Au	Ag	Sb	Bi	As	Cu	Pb	Zn	Fe%	Mn	Cr			
63712	Chip	7.0	13.6	1.9	6.6	5	X	X	X	3	X	30	235	90	140	8.85	495	75	Gossanous chips in broken Lithic Wacke. Pyrite-mag-haem. vein in broken chloritic wacke.		
713	"	13.6	16.6	1.9	3.0	X	15	X	X	5	X	81	365	485	295	8.55	5100	30			
714	"	16.6	19.6	3.0	3.0	X	12	X	X	11	X	12	280	90	225	8.35	1650	60			
715	"	19.6	22.4	2.8	2.8	X	15	X	X	X	X	1	210	65	235	11.00	2150	85			
716	"	22.4	24.5	2.1	2.1	7	18	X	X	X	X	19	170	360	600	12.50	1650	60			
717	"	24.5	26.9	1.8	2.4	20	26	X	X	5	X	38	210	270	415	10.50	1450	80			
718	"	26.9	29.6	1.1	2.7	X	16	X	X	X	X	8	135	340	275	6.65	645	50			
719	"	29.6	32.1	1.6	2.5	9	11	X	X	3	X	40	160	700	225	6.10	870	55			
63720	"	32.1	34.8	0.8	2.7	7	X	X	X	9	X	10	115	80	260	8.70	945	60			
721	Split	34.8	35.45	0.65	0.65	194	7	X	X	X	20	18	315	25	205	15.5	6050	50			
722	"	35.45	35.8	0.35	0.35	5	20	X	X	4	X	15	95	95	635	4.65	4000	35			
723	"	35.8	36.5	0.7	0.7	5	130	X	2.0	18	X	30	130	720	2150	8.95	3450	60			
724	"	36.5	37.35	0.75	0.85	270	41	0.02	X	18	20	1350	1500	10	160	20.5	4200	75			
725	"	37.35	37.5	0.15	0.15	1.82%	829	0.34	1.5	109	60	4.30%	2350	60	170	25.0	1700	105			
726	"	37.5	38.0	0.5	0.05	55	38	X	X	11	X	130	555	15	260	14.5	2200	105			
727	Chip	38.0	40.0	1.70	2.0	234	10	X	X	X	X	9	65	X	175	12.0	1850	115			
728	"	40.0	42.5	2.5	2.5	16	17	X	X	X	X	X	35	X	280	7.10	1150	145			
729	"	42.5	44.3	1.8	1.8	7	13	0.01	X	X	X	1	75	5	315	7.55	1000	120			
63730	"	44.3	45.6	1.2	1.3	X	15	0.04	X	X	X	X	90	X	245	6.40	1950	85			
731	Split	45.6	46.2	0.6	0.6	X	10	X	X	X	X	13	165	X	315	7.50	1300	100			
732	"	46.2	46.5	0.3	0.3	21	X	0.01	X	13	X	18	1200	35	175	11.00	2800	60			
733	"	46.5	47.2	0.7	0.7	3140	155	0.04	7.0	7	140	270	980	125	245	11.50	29.50	70			
734	Chip	47.2	50.4	3.2	3.2	26	21	0.02	X	3	X	14	475	X	210	8.90	1550	90			
735	"	50.4	51.85	1.35	1.45	115	12	X	0.5	11	60	77	465	5	195	16.50	2450	60			
736	"	51.85	54.25	2.4	2.4	22	X	X	X	3	X	7	235	X	230	11.00	1750	90			
737	Split	54.25	54.55	0.3	0.3	X	X	X	X	X	X	1	140	X	155	5.35	1000	85			
738	"	54.55	55.15	0.6	0.6	X	X	X	X	X	X	X	65	X	270	8.45	810	105			
739	"	55.15	55.5	0.35	0.35	X	X	X	X	X	X	X	140	X	230	6.80	855	90			
63740	"	55.5	56.0	0.5	0.5	X	X	0.03	X	X	X	X	400	X	220	7.45	965	75			
741	"	56.0	57.0	1.0	1.0	X	X	X	X	X	X	X	100	X	140	7.60	825	75			
742	"	57.0	57.6	0.6	0.6	5	X	X	X	5	X	X	100	X	140	6.25	915	70			
743	"	57.6	58.5	0.9	0.9	16	X	X	X	6	X	X	20	X	145	6.05	1100	100			
744	Chip	58.5	60.0	1.5	1.5	X	X	X	X	X	X	X	15	X	170	7.15	685	55			
745	"	60.0	63.0	3.0	3.0	53	11	X	X	5	X	X	50	20	280	7.70	705	50			
746	"	63.0	66.0	3.0	3.0	25	X	X	X	X	X	X	40	X	190	6.90	885	105			
747	"	66.0	68.2	2.2	2.2	39	14	X	X	8	X	5	70	X	175	8.95	1150	100			
748	"	68.2	71.0	2.8	2.8	X	X	X	X	X	X	X	35	X	195	8.55	935	90			
749	"	71.0	73.8	2.8	2.8	14	X	X	X	9	X	X	785	X	170	7.60	800	60			
63750	"	73.8	76.7	2.9	2.9	31	12	X	X	5	X	X	30	X	195	8.10	790	60			
751	"	76.7	79.0	2.3	2.3	14	X	X	X	X	X	X	75	X	200	8.30	895	60			
752	"	79.0	81.0	2.0	2.0	8	X	X	X	X	X	X	15	X	220	8.50	1050	80			
753	"	81.0	83.8	2.8	2.8	X	X	X	X	X	X	X	30	X	230	8.50	1050	80			
754	"	83.8	86.9	3.1	3.1	X	X	0.11	X	X	X	X	375	X	205	6.75	970	65			
																			Pyrite-pyrrhotite-(chalcopyrite) stringers		
																			Contains 0.3m fracture zone with qtz-cb crackle veins.		