

531

ELECTROLYTIC ZINC COMPANY OF A'ASIA LTD.
MINERAL RESOURCES DIVISION - TASMANIA

DIAMOND DRILL CORE GEOCHEMICAL ANALYSES RECORD

HOLE No. CHP 264
SHEET No. 2

Sample No.	Sample Type	From	To	Core Rec'd	Sample Length	METAL CONTENT (ppm unless specified)														COMMENTS
						Sn	W	Au	Ag	Sb	Bi	As	Cu	Pb	Zn	Fe%	Mn	Cr		
63144	Chip	114.0	115.2	1.2	1.2	5	12	X	X	9	X	12	30	20	50	3.65	1150	25		
145	"	115.2	117.8	2.6	2.6	5	X	X	X	X	X	4	55	20	90	5.70	1250	40		
146	"	117.8	120.0	2.2	2.2	X	X	X	X	X	X	5	80	20	115	7.35	1300	60		
147	"	120.0	121.8	1.8	1.8	X	X	X	X	6	X	3	75	25	90	5.75	1250	55		
148	"	121.8	124.0	2.2	2.2	X	X	X	X	X	X	2	15	20	75	5.05	1050	30		
149	"	124.0	127.0	3.0	3.0	2	X	X	X	X	X	19	85	35	70	5.85	3150	95		
63150	"	127.0	129.8	2.8	2.8	X	X	X	X	6	X	13	105	20	90	6.05	1150	95		
151	"	129.8	132.7	2.9	2.9	5	X	X	X	4	X	35	95	20	125	8.50	3250	80		
152	"	132.7	136.0	3.1	3.3	6	10	X	X	X	X	38	35	20	105	8.00	3200	35		
153	"	136.0	139.4	3.4	3.4	X	X	X	X	4	X	10	80	45	170	6.30	1250	55		
154	"	139.4	141.5	2.1	2.1	X	X	X	X	19	X	38	135	70	125	2.10	950	20		
155	"	141.5	143.4	1.9	1.9	X	X	X	X	X	X	11	120	20	155	6.05	775	40		
156	Split	143.4	144.0	0.6	0.6	2	14	X	X	4	X	10	120	20	120	7.15	1300	65		
157	"	144.0	144.5	0.5	0.5	X	X	X	X	X	X	0	45	30	130	5.85	1650	75		
158	"	144.5	145.2	0.7	0.7	X	X	X	X	X	X	10	40	20	75	5.35	1400	120		
159	"	145.2	145.85	0.65	0.65	X	X	X	X	X	X	7	15	25	90	5.60	1650	20		
63160	Split	145.85	146.7	0.85	0.85	X	X	X	X	X	X	4	25	30	70	4.10	1800	80		
161	Chip	146.7	149.7	3.0	3.0	X	X	X	X	X	X	4	5	25	115	7.15	1300	100		
162	"	149.7	152.4	2.7	2.7	X	X	X	X	3	X	X	10	25	125	8.00	950	160		
163	Split	152.4	153.15	0.75	0.75	X	X	X	X	X	X	1	X	35	115	5.60	1650	65		
164	"	153.15	154.1	0.95	0.95	X	X	X	X	X	X	5	25	105	6.40	1750	40			
165	"	154.1	155.1	1.0	1.0	X	10	X	X	X	X	1	5	15	90	6.20	1350	55		
166	"	155.1	156.1	1.0	1.0	X	14	X	X	X	X	5	15	20	85	6.45	1300	30		
167	"	156.1	156.8	0.7	0.7	4	X	X	X	4	X	15	20	20	80	7.20	3200	55		
168	"	156.8	157.8	1.0	1.0	X	X	X	X	X	X	7	5	25	85	5.90	1800	55		
169	"	157.8	158.8	1.0	1.0	X	X	X	X	X	X	X	5	25	85	5.85	1850	35		
63170	"	158.8	159.5	0.7	0.7	X	12	X	X	X	X	5	25	25	80	6.20	1900	50		
171	"	159.5	160.1	0.6	0.6	X	X	X	X	X	X	2	5	30	85	5.75	2000	80		
172	"	160.1	160.8	0.7	0.7	X	X	X	X	3	X	4	15	25	65	5.85	1750	40		
173	Split	160.8	161.9	1.1	1.1	X	10	X	X	6	X	18	45	20	80	6.55	1850	75		
174	Chip	161.9	164.5	2.6	2.6	X	X	X	0.5	15	X	17	75	45	80	5.50	1250	75		
175	"	164.5	167.5	3.0	3.0	X	X	X	0.5	11	X	18	75	55	110	7.75	1650	55		
176	"	167.5	170.5	3.0	3.0	X	10	X	1.0	12	X	32	190	65	110	5.50	780	75		
177	"	170.5	173.5	3.0	3.0	4	X	X	1.0	22	X	32	170	30	80	6.90	3200	145		
178	"	173.5	176.5	3.0	3.0	X	X	X	1.0	32	X	52	100	55	75	5.00	860	75		
179	"	176.5	178.9	2.4	2.4	X	X	X	X	X	X	6	45	15	90	7.60	795	180		
63180	"	178.9	180.5	1.6	1.6	2	X	X	X	X	X	2	5	15	120	7.00	870	325		
181	"	180.5	183.0	2.5	2.5	X	X	X	X	X	X	1	105	15	125	6.45	455	85		
182	"	183.0	185.2	2.2	2.2	X	12	X	X	5	X	10	130	20	150	7.75	475	155		
183	"	185.2	188.0	2.8	2.8	6	X	X	X	4	X	4	10	10	115	7.30	1900	140		
184	"	188.0	190.3	2.3	2.3	X	X	X	X	5	X	3	5	15	105	8.20	2150	50		
185	"	190.3	192.4	2.1	2.1	X	X	X	0.5	X	X	5	45	20	115	7.25	1500	50		
186	"	192.4	194.8	2.4	2.4	X	X	X	0.5	X	X	13	170	30	135	7.20	915	50		
187	"	194.8	196.7	1.9	1.9	X	13	X	X	X	X	2	10	15	125	6.90	640	220		
188	"	196.7	198.7	2.0	2.0	X	X	X	X	X	X	3	10	20	155	7.45	620	335		
189	"	198.7	201.7	3.0	3.0	X	X	X	X	X	X	4	5	25	115	6.85	1850	305		
63190	"	201.7	203.2	1.5	1.5	X	X	X	0.5	X	X	2	5	15	150	6.50	1800	150		
191	"	203.2	205.1	1.9	1.9	X	10	X	X	4	X	X	5	20	95	5.35	580	190		
192	"	205.1	207.1	2.0	2.0	5	X	X	X	6	X	19	80	15	120	9.00	2700	95		
193	"	207.1	209.1	2.0	2.0	2	X	X	0.5	17	X	9	90	25	105	7.45	965	125		
194	"	209.1	211.6	2.5	2.5	X	X	X	0.5	13	X	9	30	10	105	6.70	715	110		
195	"	211.6	213.4	1.8	1.8	X	X	X	0.5	14	X	19	135	25	110	8.00	1600	125		

251531