

CORE GRIND SAMPLING

HOLE No. MAC-26

DATE 11/1/90

No.	SAMPLE NUMBER	INTERVAL	ELEMENTS REQUIRED	ST	SAMPLE NUMBER	INTERVAL	ELEMENTS REQUIRED
1	562416	0-14.2			562448	209.8-212.2	
2	417	14.2-23.5			449	212.2-215.8	
3	418	23.5-25.6			450	215.8-217.0	SPLIT CORE
4	419	25.6-29.4			431363	217.0-218.4	"
5	420	29.4-43.0			387	218.4-220.0	"
6	421	43.0-50.9			388	220.0-221.0	"
7	422	50.9-58.4			398	221.0-222.0	"
8	423	58.4-68.2			399	222.0-223.0	"
9	424	68.2-77.3			400	223.0-224.0	"
10	425	77.3-76.2			562460	224.0-225.3	"
11	426	76.2-85.2			461	225.3-233.2	
12	427	85.2-96.0			462	233.2-235.0	
13	428	96.0-98.5			463	235.0-238.1	
14	429	98.5-103.6			464	238.1-245.7	
15	430	103.6-106.2			465	245.7-247.0	SPLIT CORE
16	431	106.2-114.2			516212	247.0-248.0	"
17	432	114.2-124.4			214	248.0-249.0	"
18	433	124.4-130.6			562466	249.0-251.6	
19	434	130.6-139.8			467	251.6-262.9	
20	435	139.8-142.4			468	262.9-268.1	
21	436	142.4-150.0			469	268.1-274.8	
22	437	150.0-156.0			470	274.8-277.7	
23	438	156.0-169.7			471	277.7-288.5	
24	439	169.7-175.9			472	288.5-295.0	
25	440	STANDARD *			473	295.0-304.4	
26	441	175.9-179.7			474	304.4-308.7	
27	442	179.7-184.8			475	308.7-312.4	
28	443	184.8-191.2			476	312.4-325.8	
29	444	191.2-197.4			477	325.8-337.1	
30	445	197.4-202.3			478	337.1-340.1	
31	446	202.3-206.5			479	340.1-353.4	
32	447	206.5-209.8			480	353.4-358.7	