

TASMANIAN CONSTRUCTION MATERIALS REGISTER

Serial No. 43 (b) Grid Reference 088 648 Map Sheet No 82

Name of Owner/Quarry: A. N. M - Boyer (east)

Working Pit/Disused Pit/New Locality: Frequent Use.

Past Production: 9,000 m³ Estimated Reserves: moderate.

Description of site: Pit dug into same gully as 43 (a), but 250 m close to the Derwent. Same access.

Limits to expansion: Topographical constraints

Thickness of overburden: 10-20 cm

Sources of information: RAAM Field: 10/10/78 Laboratory: _____ Ref. No.: _____

Sizing analysis: _____ Date: _____

mm	76.2	50.8	38.1	25.4	19.0	9.53	4.76	2.36	1.18	0.60	0.425	0.30	0.15	0.075	0.038
	75.0	53.0	37.5	26.5											
1		100	93		84	73	62	55	49	44		39	31	25	21
2		0	7		16	27	38	45	51	56		61	69	75	79
3		0	7		9	11	11	7	6	5		5	8	6	4
4															

L.L. _____ P.I. _____ L.S. _____ D.R. _____

Special tests: _____

Group Symbol (unified soil classification system): _____

Geological Description: Permian gravel, higher silt content than 43 (a).

History: Being used at present by contractors for logging sites at the paper mill.

Remarks: Sampled material being used.

12