

S3 88067 784P/M 236088

TASMANIAN CONSTRUCTION MATERIALS REGISTER

Serial No. S3* Grid Reference 384 356 Map Sheet No 88

Name of Owner/Quarry: G.L. Males - Collins Springs

Working Pit/~~Disused Pit~~/~~New~~ Locality: Frequently worked

Past Production: ≈ 100,000 m³ Estimated Reserves: Moderate

Description of site: Large sand pit amidst scrubby vegetation to the west of Goat Bluff.

Limits to expansion: South Arm Road, Sand dunes (different sand type)

Thickness of overburden: Variable thickness

Sources of information: RAMPR Field: 10/1/79 Laboratory: _____ Ref. No.: _____

Sizing analysis: _____ Date: _____

mm	76.2	50.8	38.1	25.4	12.0	9.53	4.76	2.36	1.18	0.60	0.425	0.30	0.15	0.075	0.038
1										100		98	21	3	0
2							100	99	89	67	45	31	7	1	0
3															
4															

*5
9

L.L. _____ P.I. _____ L.S. _____ D.R. _____

Special tests: _____

Group Symbol (unified soil classification system): SW-SP

Geological Description: Medium to coarse white, yellow and light grey sands. Also illuviated areas.

History: Worked for many years on a relatively small scale - supplying Hobart with coarse sand. Worked with dozer and suction pump. Down to below the water table.

Remarks: Main Pit - 5x80x200 = 80,000

Small pits - average depth 1m. = ≈ 20,000.

Sampled.

* Sample submitted for hot mix